

RECEIVED JUN 26 2015

## SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: EPOXY RESIN PT-A Product Code: #A 9100

**SUPPLIER:**

**Hastings Fiber Glass Products, Inc**  
**770 Cook Rd**  
**Hastings, MI 49058**

**MANUFACTURER:**

**Hastings Fiber Glass Products, Inc**  
**770 Cook Rd**  
**Hastings, MI 49058**

24 hours

**Emergency telephone: 800-373-7542**  
**24 hours**

Product Use:

Not recommended for:

## SECTION 2 - HAZARDS IDENTIFICATION

NEPA Ratings, risks phrases and suggested HMIS Hazards Categories:

**GHS Ratings:**

Skin corrosive	3
Eye corrosive	1
Reproductive toxin	2

Reversible adverse effects in dermal tissue, Draize score:  $\geq 1.5 < 2.3$   
 Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity  $\geq 3$ , Iritis  $> 1.5$   
 Human or animal evidence possibly with other information

**GHS Hazards**

H316	Causes mild skin irritation
H318	Causes serious eye damage
H361	Suspected of damaging fertility or the unborn child

**GHS Precautions**

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P310	Immediately call a POISON CENTER or doctor/physician
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice/attention
P405	Store locked up
P501	Dispose of contents/container in accordance with Local, State and Federal Regulations.

Danger



### SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Acetone 67-64-1	1000 ppm TWA; 2400 mg/m <sup>3</sup> TWA	750 ppm STEL 500 ppm TWA	NIOSH: 250 ppm TWA; 590 mg/m <sup>3</sup> TWA
n-Butyl acetate 123-86-4	150 ppm TWA; 710 mg/m <sup>3</sup> TWA	200 ppm STEL 150 ppm TWA	NIOSH: 150 ppm TWA; 710 mg/m <sup>3</sup> TWA 200 ppm STEL; 950 mg/m <sup>3</sup> STEL

### SECTION 4 - FIRST AID MEASURES

**INHALATION:** Remove to FRESH air. If breathing is difficult, administer oxygen. If not breathing, give artificial respiration, preferably mouth-to-mouth. GET MEDICAL ATTENTION IMMEDIATELY.

**EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Tilt head to avoid contaminating unaffected eye. Get immediate medical attention. Remove contact lenses if possible.

**SKIN CONTACT:** Flush skin with plenty of water while removing contaminated clothing and shoes. Do not reuse clothing or shoes until cleaned. If irritation develops or persists, get medical attention. Discard contaminated leather articles such as shoes and belt. Do not apply oils or ointments unless ordered by the physician.

**INGESTION:** If fully conscious, give two glasses of water, then induce vomiting by touching back of throat with finger. Keep head below hips to prevent aspiration of liquid into the lungs. CALL A PHYSICIAN immediately. Never induce vomiting or give anything by mouth to an unconscious victim.

**NOTE TO PHYSICIANS:** There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. Individuals experiencing breathing difficulties after exposure to vapor generated in aerosol applications should be observed for at least 48 hours in case delayed respiratory complications develop.

### SECTION 5 - FIRE FIGHTING MEASURES

LEL: 1.00

UEL:

Flammable Limits: Highly flammable liquid and vapor (GHS Category 2)

Extinguishing Media: Alcohol Foam CO<sub>2</sub> Dry Chemical Foam Water Fog

Unusual Fire and Explosion Hazards: Keep containers tightly closed. Isolate from heat, sparks, and open flame. Closed

containers may explode when exposed to extreme heat. Do not use when smoking or where electrical sparks or open flame is present.  
 Haz. Combust. Products: Burning can produce carbon-dioxide and/or carbon monoxide.  
 Fire Fighting: Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.  
 Fire Equipment: As in a fire, always wear self-contained breathing apparatus in pressure-demand (MSA/NIOSH approved or equivalent), and full protective gear.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

**SPILL AND LEAK PROCEDURES:**  
 Spill supervisor: Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

Small Spills: Absorb spilled liquid with sorbent pads, socks, or other inert material such as vermiculite, sand, or earth.  
 Large Spills: Avoid run-off into storm sewers and ditches that lead to waterways. Use only non-sparking tools and equipment. A vapor suppressing foam may be used. Approach the spill from upwind and pick up absorbent material and place it in a suitable container. Disposal should be in accordance with Local, State, and Federal Regulations.

**SECTION 7 - HANDLING AND STORAGE**

**HANDLING PRECAUTIONS:**  
 Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).  
**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: GROUNDING:** when transferring, fill stem and container must be grounded and bonded. Store in a cool dry area with ventilation suitable for storing materials shown in section II. Keep away from heat, sparks and open flame. Do not cut, weld, braze, solder, drill, grind or expose empty containers to heat, flame, sparks or other sources of ignition; they may explode and cause injury or death.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Acetone 67-64-1	1000 ppm TWA; 2400 mg/m <sup>3</sup> TWA	750 ppm STEL 500 ppm TWA	NIOSH: 250 ppm TWA; 590 mg/m <sup>3</sup> TWA
n-Butyl acetate 123-86-4	150 ppm TWA; 710 mg/m <sup>3</sup> TWA	200 ppm STEL 150 ppm TWA	NIOSH: 150 ppm TWA; 710 mg/m <sup>3</sup> TWA 200 ppm STEL; 950 mg/m <sup>3</sup> STEL

**ENGINEERING:** Ensure processing (curing) ovens are properly vented to prevent the introduction of processing fumes into the work place. Use

explosion proof equipment and good manufacturing practice. Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGHIS TLV limit. OTHER PRECAUTIONS: Provide respiratory protection against fumes generated during burning. Avoid prolonged contact with skin and breathing of vapors.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

This mixture typically exhibits the following properties under normal circumstances:

<b>Boiling range:</b> Not Applicable <b>Evaporation rate:</b> Not Applicable <b>Explosive Limits:</b> Not Applicable  <b>Autoignition temperature:</b> Not Applicable <b>Viscosity:</b> Not Applicable <b>Appearance:</b> Not Applicable <b>Vapor Pressure:</b> -99999 mmHg <b>Vapor Density:</b> 2.4 <b>Specific Gravity:</b> 1.184028316 <b>Freezing point:</b> Not Applicable	<b>Flash point:</b> -4 F,-20 C <b>Flammability:</b> Not Applicable <b>Partition coefficient (n-octanol/water):</b> Not Applicable <b>Decomposition temperature:</b> Not Applicable <b>Grams VOC less water:</b> Not Applicable <b>Odor:</b> Not Applicable <b>Odor threshold:</b> Not Applicable <b>pH:</b> Not Applicable <b>Melting point:</b> Not Applicable <b>Solubility:</b> Not Applicable
--	--

**SECTION 10 - STABILITY AND REACTIVITY**

Stability:

STABLE

Components of this mixture are incompatible with the following materials:

No Data Found

This mixture is likely to exhibit the following combustion products:

No Data Found

Hazardous polymerization will not occur.

**SECTION 11- TOXICOLOGICAL INFORMATION**

**Mixture Toxicity**

Inhalation Toxicity LC50: 216mg/L

**Component Toxicity**

Toxicological Information: No data found.

ROUTES OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Contact

No Data Found

Exposure to this material may affect the following organs:

- Eyes
- Central Nervous System
- Skin
- Respiratory System

**Effects of Overexposure**

**Carcinogenicity:**

The following chemicals comprise 0.1% or more of this mixture and are listed and / or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA.

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
None			No Data Found

**SECTION 12 - ECOLOGICAL INFORMATION**

Ecological information: No data found.

**Component Ecotoxicity**

Acetone	96 Hr LC50 Oncorhynchus mykiss: 4.74 - 6.33 mL/L; 96 Hr LC50 Pimephales promelas: 6210 - 8120 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 8300 mg/L 48 Hr EC50 Daphnia magna: 10294 - 17704 mg/L [Static]; 48 Hr EC50 Daphnia magna: 12600 - 12700 mg/L
n-Butyl acetate	96 Hr LC50 Lepomis macrochirus: 100 mg/L [static]; 96 Hr LC50 Pimephales promelas: 17 - 19 mg/L [flow-through] 72 Hr EC50 Desmodesmus subspicatus: 674.7 mg/L

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Material that cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. State and local disposal regulations may differ from federal disposal definitions found in 40 CFR 261.3. Dispose of container and unused contents in accordance with federal, state and local requirements.

**SECTION 14 - TRANSPORT INFORMATION**

This material is classified for transport as follows:

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
	No Data Found			

**SECTION 15 - REGULATORY INFORMATION**

Additional regulatory listings, where applicable.

**State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!**  
This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None

This product contains the following substances subject to the reporting requirements of Section 313 of Title II of the Superfund Amendments and Reauthorization Act of 1986 and CFR Part 40

- None

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>

EU Risk Phrases

Safety Phrase

<b>SECTION 16 - OTHER INFORMATION</b>
---------------------------------------

**Hazardous Material Information System (HMIS)**

<b>HEALTH</b>	2
<b>FLAMMABILITY</b>	3
<b>PERSONAL PROTECTION</b>	1

**HMIS & NFPA Hazard Rating****Legend**


\* = Chronic Health Hazard

0 = INSIGNIFICANT

1 = SLIGHT

2 = MODERATE

3 = HIGH

**National Fire Protection Association (NFPA)**

Date Prepared: 5/12/2015

Reviewer/Revision

The information contained on this SDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.

A30101

SAFETY DATA SHEET 10-100

Clear Part B

RECEIVED JUN 26 2015

## SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: EPOXY CATALYST PT-B Product Code: #B9000

**SUPPLIER:**

**Hastings Fiber Glass Products, Inc**  
**770 Cook Rd**  
**Hastings, MI 49058**  
**24 hours**

**MANUFACTURER:**

**Hastings Fiber Glass Products, Inc**  
**770 Cook Rd**  
**Hastings, MI 49058**  
**Emergency telephone: 800-373-7542**  
**24 hours**

Product Use:

Not recommended for:

## SECTION 2 - HAZARDS IDENTIFICATION

NEPA Ratings, risks phrases and suggested HMIS Hazards Categories:

**GHS Ratings:**

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Skin corrosive	1C	Destruction of dermal tissue: Exposure < 4 hours
		Observation < 14 days, visible necrosis in at least one animal
Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5
Skin sensitizer	1	Skin sensitizer
Reproductive toxin	2	Human or animal evidence possibly with other information

**GHS Hazards**

H225	Highly flammable liquid and vapour
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H361	Suspected of damaging fertility or the unborn child

**GHS Precautions**

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/light/.../equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P260	Do not breathe dust/fume/gas/mist/vapours/spray
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P264	Wash ... thoroughly after handling
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/protective clothing/eye protection/face protection

P281	Use personal protective equipment as required
P310	Immediately call a POISON CENTER or doctor/physician
P321	Specific treatment (see ... on this label)
P363	Wash contaminated clothing before reuse
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P302+P352	IF ON SKIN: Wash with soap and water
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P333+P313	If skin irritation or a rash occurs: Get medical advice/attention
P370+P378	In case of fire: Use ... for extinction
P405	Store locked up
P403+P235	Store in a well ventilated place. Keep cool
P501	Dispose of contents/container in accordance with Local, State and Federal Regulations.

Danger



### SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Isopropyl alcohol 67-63-0	400 ppm TWA; 980 mg/m <sup>3</sup> TWA	400 ppm STEL 200 ppm TWA	NIOSH: 400 ppm TWA; 980 mg/m <sup>3</sup> TWA 500 ppm STEL; 1225 mg/m <sup>3</sup> STEL

### SECTION 4 - FIRST AID MEASURES

INHALATION: Remove to FRESH air. If breathing is difficult, administer oxygen. If not breathing, give artificial respiration, preferably mouth-to-mouth: GET MEDICAL ATTENTION IMMEDIATELY.



**EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Tilt head to avoid contaminating unaffected eye. Get immediate medical attention. Remove contact lenses if possible.

**SKIN CONTACT:** Flush skin with plenty of water while removing contaminated clothing and shoes. Do not reuse clothing or shoes until cleaned. If irritation develops or persists, get medical attention. Discard contaminated leather articles such as shoes and belt. Do not apply oils or ointments unless ordered by the physician.

**INGESTION:** If fully conscious, give two glasses of water, then induce vomiting by touching back of throat with finger. Keep head below hips to prevent aspiration of liquid into the lungs. **CALL A PHYSICIAN** immediately. Never induce vomiting or give anything by mouth to an unconscious victim.

**NOTE TO PHYSICIANS:** There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. Individuals experiencing breathing difficulties after exposure to vapor generated in aerosol applications should be observed for at least 48 hours in case delayed respiratory complications develop.

## SECTION 5 - FIRE FIGHTING MEASURES

**LEL:** 3.00

**UEL:**

**Flammable Limits:** Highly flammable liquid and vapor (GHS Category 2)

**Extinguishing Media:** Alcohol Foam CO2 Dry Chemical Foam Water Fog

**Unusual Fire and Explosion Hazards:** Keep containers tightly closed. Isolate from heat, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Do not use when smoking or where electrical sparks or open flame is present.

**Haz. Combust. Products:** Burning can produce carbon-dioxide and/or carbon monoxide.

**Fire Fighting:** Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

**Fire Equipment:** As in a fire, always wear self-contained breathing apparatus in pressure-demand (MSA/NIOSH approved or equivalent), and full protective gear.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

### SPILL AND LEAK PROCEDURES:

**Spill supervisor:** Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

**Small Spills:** Absorb spilled liquid with sorbent pads, socks, or other inert material such as vermiculite, sand, or earth.

**Large Spills:** Avoid run-off into storm sewers and ditches that lead to waterways. Use only non-sparking tools and equipment. A vapor suppressing foam may be used. Approach the spill from upwind and pick up absorbent material and place it in a suitable container. Disposal should be in accordance with Local, State, and Federal Regulations.

## SECTION 7 - HANDLING AND STORAGE

### HANDLING PRECAUTIONS:

Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures, i.e., 40 to 95 F (4 to 35 C).

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: GROUNDING:** when transferring, fill stem and container must be grounded and bonded. Store in a cool dry area with ventilation suitable for storing materials shown in section II. Keep away from heat, sparks and open flame. Do not cut, weld,

braze, solder, drill, grind or expose empty containers to heat, flame, sparks or other sources of ignition; they may explode and cause injury or death.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Isopropyl alcohol 67-63-0	400 ppm TWA; 980 mg/m3 TWA	400 ppm STEL 200 ppm TWA	NIOSH: 400 ppm TWA; 980 mg/m3 TWA 500 ppm STEL; 1225 mg/m3 STEL

**ENGINEERING:** Ensure processing (curing) ovens are properly vented to prevent the introduction of processing fumes into the work place. Use explosion proof equipment and good manufacturing practice.

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH's TLV limit.

**OTHER PRECAUTIONS:** Provide respiratory protection against fumes generated during burning. Avoid prolonged contact with skin and breathing of vapors.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

This mixture typically exhibits the following properties under normal circumstances:

<p align="center"><b>Appearance</b> Liquid dispersion</p> <p align="center"><b>Vapor Pressure:</b> -99999 mmHg</p> <p align="center"><b>Vapor Density</b> Heavier than air</p> <p align="center">SG 1.00</p> <p align="center"><b>Freezing point:</b> Not Applicable</p> <p align="center"><b>Boiling range:</b> 83°C</p> <p align="center"><b>Evaporation Rate</b> Slower than ether</p> <p align="center"><b>Autoignition temperature:</b> Not Applicable</p> <p align="center"><b>Viscosity:</b> Not Applicable</p> <p align="center"><b>Fragrance VOC</b> 30.00</p>	<p align="center"><b>Odor</b> Solvent</p> <p align="center"><b>Odor threshold:</b> Not Applicable</p> <p align="center"><b>pH:</b> Not Applicable</p> <p align="center"><b>Melting point:</b> Not Applicable</p> <p align="center"><b>Solubility:</b> Not Applicable</p> <p align="center"><b>Flash point:</b> 11 C, 52 F</p> <p align="center"><b>Physical State</b> Liquid</p> <p align="center"><b>Decomposition temperature:</b> Not Applicable</p> <p align="center"><b>Boiling Point</b> 83°C</p> <p align="center"><b>ACTUAL VOC</b> 224.430</p>
---	---

**SECTION 10 - STABILITY AND REACTIVITY**

Stability:

STABLE

Components of this mixture are incompatible with the following materials:

No Data Found

This mixture is likely to exhibit the following combustion products:

No Data Found

Hazardous polymerization will not occur.

**SECTION 11- TOXICOLOGICAL INFORMATION**

**Mixture Toxicity****Component Toxicity**

67-63-0

Isopropyl alcohol

Oral LD50: 4,396 mg/kg (Rat)

Toxicological Information: No data found.

ROUTES OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Contact

**No Data Found**

Exposure to this material may affect the following organs:

**Eyes      Skin      Respiratory System****Effects of Overexposure****Carcinogenicity:**

The following chemicals comprise 0.1% or more of this mixture and are listed and / or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA.

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
None			No Data Found

**SECTION 12 - ECOLOGICAL INFORMATION**

Ecological information: No data found.

**Component Ecotoxicity**

Isopropyl alcohol

96 Hr LC50 Pimephales promelas: 9640 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: 11130 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: >1400000 µg/L  
 48 Hr EC50 Daphnia magna: 13299mg/L  
 96 Hr EC50 Desmodesmus subspicatus: >1000 mg/L; 72 Hr EC50 Desmodesmus subspicatus: >1000mg/L

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Material that cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. State and local disposal regulations may differ from federal disposal definitions found in 40 CFR 261.3. Dispose of container and unused contents in accordance with federal, state and local requirements.

**SECTION 14 - TRANSPORT INFORMATION**

This material is classified for transport as follows:

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	UN1263, PAINT RELATED MATERIAL	1263	II	3
IATA	UN1263, PAINT RELATED MATERIAL	1263	II	3
IMDG	UN1263, PAINT RELATED MATERIAL	1263	II	3

**SECTION 15 - REGULATORY INFORMATION**

Additional regulatory listings, where applicable.

**State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!**

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None

This product contains the following substances subject to the reporting requirements of Section 313 of Title II of the Superfund Amendments and Reauthorization Act of 1986 and CFR Part 40

Country

Regulation

All Components Listed

EU Risk Phrases

Safety Phrase

- None


**SECTION 16 - OTHER INFORMATION**

**Hazardous Material Information System (HMIS)**

HEALTH	2
FLAMMABILITY	3
PERSONAL PROTECTION	1

**HMIS & NFPA Hazard Rating Legend**  
 \* = Chronic Health Hazard  
 0 = INSIGNIFICANT  
 1 = SLIGHT  
 2 = MODERATE  
 3 = HIGH

**National Fire Protection Association (NFPA)**



Date Prepared: 5/14/2015

Reviewer Revision

The information contained on this SDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.

T71100  
A30109

**SAFETY DATA SHEET**

10-100

Thinner

10-101

RECEIVED JUN 26 2015

**SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Product Name: #711 THINNER . Product Code: T711

**SUPPLIER:**

**Hastings Fiber Glass Products, Inc**  
770 Cook Rd  
Hastings, MI 49058

Emergency telephone: 800-373-7542  
24 hours

**MANUFACTURER:**

**Hastings Fiber Glass Products, Inc**  
770 Cook Rd  
Hastings, MI 49058

Emergency telephone: 800-373-7542  
24 hours

Product Use:

Not recommended for:

**SECTION 2 - HAZARDS IDENTIFICATION**

NEPA Ratings, risks phrases and suggested HMIS Hazards Categories:

**GHS Ratings:**

Flammable liquid	2	Flash point $\leq 23^{\circ}\text{C}$ and initial boiling point $> 35^{\circ}\text{C}$ (95°F)
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: $\geq 2.3 < 4.0$ or persistent inflammation
Eye corrosive	2A	Eye irritant: Subcategory 2A; Reversible in 21 days
Mutagen	1B	Known to produce heritable mutations in human germ cells Subcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity
Carcinogen	1B	Presumed Human Carcinogen, Based on demonstrated animal carcinogenicity
Reproductive toxin	2	Human or animal evidence possibly with other information
Aspiration hazard	1	Aspiration Toxicity Category 1: Known (regarded)- human evidence - hydrocarbons with kinematic viscosity $\geq 20.5$ mm <sup>2</sup> /s at 40°C.

**GHS Hazards**

H225	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H340	May cause genetic defects
H350	May cause cancer
H361	Suspected of damaging fertility or the unborn child

**GHS Precautions**

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat/sparks/open flames/hot surfaces - No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/light/equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P264	Wash hands thoroughly after handling

P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P321	Specific treatment (see directions on this label)
P331	Do NOT induce vomiting
P362	Take off contaminated clothing and wash before reuse
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P302+P352	IF ON SKIN: Wash with soap and water
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P332+P313	If skin irritation occurs: Get medical advice/attention
P337+P313	Get medical advice/attention
P370+P378	In case of fire: Use dry chemical (BC) or carbon dioxide (Co2) for extinction
P405	Store locked up
P403+P235	Store in a well ventilated place. Keep cool
P501	Dispose of contents/container in accordance with Local, State and Federal Regulations.

**Signal Word: Danger**



### SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
Naphtha-Light aromatic	64742-95-6	
methyl propyl ketone	107-87-9	
2-Butoxyethanol	111-76-2	

### SECTION 4 - FIRST AID MEASURES

**INHALATION:** Remove to FRESH air. If breathing is difficult, administer oxygen. If not breathing, give artificial respiration, preferably mouth-to-mouth. GET MEDICAL ATTENTION IMMEDIATELY.

**EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Tilt head to avoid contaminating unaffected eye. Get immediate medical attention. Remove contact lenses if possible.

**SKIN CONTACT:** Flush skin with plenty of water while removing contaminated clothing and shoes. Do not reuse clothing or shoes until cleaned. If irritation develops or persists, get medical attention. Discard contaminated leather articles such as shoes and belt. Do not apply oils or ointments unless ordered by the physician.

**INGESTION:** If fully conscious, give two glasses of water, then induce vomiting by touching back of throat with finger. Keep head below hips to prevent aspiration of liquid into the lungs. CALL A PHYSICIAN immediately. Never induce vomiting or give anything by mouth to an unconscious victim.

**NOTE TO PHYSICIANS:** There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. Individuals experiencing breathing difficulties after exposure to vapor generated in aerosol applications should be observed for at least 48 hours in case delayed respiratory complications develop.

### SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: 7 C (45 F)

LEL: 1.00

Flammable Limits: Highly flammable liquid and vapor (GHS Category 2)

UEL:

Extinguishing Media: Alcohol Foam CO2 Dry Chemical Foam Water Fog

Unusual Fire and Explosion Hazards: Keep containers tightly closed. Isolate from heat, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Do not use when smoking or where electrical sparks or open flame is present.

Haz. Combust. Products: Burning can produce carbon-dioxide and/or carbon monoxide.

Fire Fighting: Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Fire Equipment: As in a fire, always wear self-contained breathing apparatus in pressure-demand (MSA/NIOSH approved or equivalent), and full protective gear.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

### SPILL AND LEAK PROCEDURES:

Spill supervisor: Ensure cleanup personnel wear all appropriate Personal Protective Equipment (PPE), including respiratory protection. Remove all ignition sources. Keep nonessential personnel away from the contaminated area.

Small Spills: Absorb spilled liquid with sorbent pads, socks, or other inert material such as vermiculite, sand, or earth.

Large Spills: Avoid run-off into storm sewers and ditches that lead to waterways. Use only non-sparking tools and equipment. A vapor suppressing foam may be used. Approach the spill from upwind and pick up absorbent material and place it in a suitable container. Disposal should be in accordance with Local, State, and Federal Regulations.

## SECTION 7 - HANDLING AND STORAGE

### HANDLING PRECAUTIONS:

Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containers closed when not in use. Do not handle or store material near heat, sparks, open flames, or other sources of ignition. Store at room temperatures i.e., 40 to 95 F (4 to 35 C).

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: GROUNDING: when transferring, fill stem and container must be grounded and bonded. Store in a cool dry area with ventilation suitable for storing materials shown in section II. Keep away from heat, sparks and open flame. Do not cut, weld, braze, solder, drill, grind or expose empty containers to heat, flame, sparks or other sources of ignition; they may explode and cause injury or death.

## SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Naphtha-Light aromatic 64742-95-6	Not Established	Not Established	Not Established
methyl propyl ketone 107-87-9	200 ppm TWA; 700 mg/m <sup>3</sup> TWA	150 ppm STEL	NIOSH: 150 ppm TWA; 530 mg/m <sup>3</sup> TWA
2-Butoxyethanol 111-76-2	50 ppm TWA; 240 mg/m <sup>3</sup> TWA	20 ppm TWA	NIOSH: 5 ppm TWA; 24 mg/m <sup>3</sup> TWA

ENGINEERING: Ensure processing (curing) ovens are properly vented to prevent the introduction of processing fumes into the work place. Use explosion proof equipment and good manufacturing practice.

Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible exposure limit or ACGIH'S TLV limit.

OTHER PRECAUTIONS: Provide respiratory protection against fumes generated during burning. Avoid prolonged contact with skin and breathing of vapors.

PROTECTIVE GEAR: Niosh/Osha approved respirator types suitable for materials in section II recommended. Approved airline type respirators or hoods recommended in confined areas. Wear protective gloves/clothing/eye/face as required.

CONTAMINATED GEAR: Take off immediately any contaminated clothing and wash it before reuse.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

This mixture typically exhibits the following properties under normal circumstances:

Appearance	Liquid dispersion	Odor	Solvent
------------	-------------------	------	---------

Vapor Pressure: -99999 mmHg	Odor threshold: Not Applicable
Vapor Density Heavier than air	pH: Not Applicable
SG 0.86	Melting point: Not Applicable
Freezing point: Not Applicable	Solubility: Not Applicable
Boiling range: 102°C	Flash point: 7 C, 45 F
Evaporation Rate Slower than ether	Physical State Liquid
Autoignition temperature: Not Applicable	Decomposition temperature: Not Applicable
Viscosity: Not Applicable	Boiling Point 102°C

**SECTION 10 - STABILITY AND REACTIVITY**

Stability:

STABLE

Components of this mixture are incompatible with the following materials:

No data found

This mixture is likely to exhibit the following combustion products:

No data found

Hazardous polymerization will not occur.

**SECTION 11- TOXICOLOGICAL INFORMATION**

**Mixture Toxicity**

Oral Toxicity LD50: 2,057mg/kg

Inhalation Toxicity LC50: 1,601mg/L

**Component Toxicity**

111-76-2

2-Butoxyethanol

Oral LD50: 1,200 mg/kg (Rat) Dermal LD50: 2,000 mg/kg (Rabbit) Inhalation LC50: 633 ppm

Toxicological Information: No data found

ROUTES OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Contact

Exposure to this material may affect the following organs:

Blood Eyes Kidneys Liver Central Nervous System Skin Respiratory System

**Effects of Overexposure**

Carcinogenicity:

The following chemicals comprise 0.1% or more of this mixture and are listed and / or classified as carcinogens or potential carcinogens by NTP, IARC, OSHA.

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
64742-95-6	Naphtha-Light aromatic		Naphtha-Light aromatic: EU REACH: Present (P)

**SECTION 12 - ECOLOGICAL INFORMATION**

Ecological information: No data found.

**Component Ecotoxicity**

Naphtha-Light aromatic

96 Hr LC50 Oncorhynchus mykiss: 9.22mg/L

48 Hr EC50 Daphnia magna: 6.14mg/L

methyl propyl ketone

96 Hr LC50 Pimephales promelas: 1190 - 1290 mg/L [flow-through]



**SECTION 13 - DISPOSAL CONSIDERATIONS**

Material that cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. State and local disposal regulations may differ from federal disposal definitions found in 40 CFR 261.3. Dispose of container and unused contents in accordance with federal, state and local requirements.

**SECTION 14 - TRANSPORT INFORMATION**

This material is classified for transport as follows:

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	UN1263,PAINT RELATED MATERIAL	1263	II	3
IATA	UN1263,PAINT RELATED MATERIAL	1263	II	3
IMDG	UN1263,PAINT RELATED MATERIAL	1263	II	3

**SECTION 15 - REGULATORY INFORMATION**

Additional regulatory listings, where applicable.

**State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!**

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None

This product contains the following substances subject to the reporting requirements of Section 313 of Title II of the Superfund Amendments and Reauthorization Act of 1986 and CFR Part 40

- None

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
----------------	-------------------	------------------------------

**EU Risk Phrases**

R11: Highly flammable

**Safety Phrase**

S16: Keep away from sources of ignition - No smoking


**SECTION 16 - OTHER INFORMATION**

**Hazardous Material Information System (HMIS)**

**National Fire Protection Association (NFPA)**

HEALTH	2
FLAMMABILITY	3
REACTIVITY	2
PERSONAL PROTECTION	1

**HMIS & NFPA Hazard Rating Legend**  
 \* = Chronic Health Hazard  
 0 = INSIGNIFICANT  
 1 = SLIGHT  
 2 = MODERATE  
 3 = HIGH



The information contained on this SDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.

Reviewer Revision

Date Prepared: 6/18/2015